



Waterproof

- **♦** Automatic battery wake-up
- **\Delta** Battery temp. compensation
- **♦** Drive inhibit/ Ignition lock
- A Remote display port
- **♦** IR-programming interface
- **♦** Universal Mains 100-240VAC

The Customized Lithium Charger Designed and built by MEC – for professionals

Built to cope with difficult tasks, in demanding environments

HF-resonance topology - the key to packing big power into a sealed IP65 enclosure. The pressure relief vent prevents the built-up of condensation. At ease with fluids, filth, hard knocks and vibrations.

## Exposure to extreme ambient temperatures

Operates still reliably at -25°C; charge current derates at > 40°C.

## Ease of providing the charger of choice

MEC and authorized distributors deliver chargers, off-the-shelf, for any type of Li-battery, any charge current or other specific requirements. Selecting the correct file from a library with ready charge profiles, for quick and easy import via the charger's IR-Interface, will render the charger the customer wants.

#### Safety

Short circuit-, overload- and reverse polarity protection

| Pmax  | Chemistry          | Cells                | lmax | Input                       | Dimensions (mm)           |
|-------|--------------------|----------------------|------|-----------------------------|---------------------------|
| 1200W | Lilonen<br>LiFePO4 | 7S - 14S<br>7S - 16S | 40A  | 100 – 240 VAC<br>50 - 60 Hz | W * D * H:<br>225*260*105 |

Any other chemistry/cell number on request



# YOUR GLOBAL PARTNER FOR POWER SOLUTIONS!

## MEC-Energietechnik GmbH

Dorfstrasse 2, 9542 Afritz am See, Austria, Europe

E-mail: office@mec-energietechnik.at Tel: +43-(0)4247 30100-0 www.mec-energietechnik.at