Lithium Battery Charger NOVA-750I

IP65 Waterproof

- Automatic battery wake-up
- Battery temp. compensation
- Drive inhibit/ Ignition lock
- Remote display port
- IR-programming interface
- Universal Mains 100-240VAC

The Customized Lithium Charger

Designed and built by MEC – for professionals.

MEC Power Solutions

Built to cope with difficult tasks, in demanding environments

HF-resonance topology - the key to packing big power into a sealed IP65 enclosure. The pressure relief vent prevents the built-up of condensation. At ease with fluids, filth, hard knocks and vibrations.

Exposure to extreme ambient temperatures

Operates still reliably at -25°C; charge current derates at > 40°C.

Ease of providing the charger of choice

MEC and authorized distributors deliver chargers, off-the-shelf, for any type of Li-battery, any charge current or other specific requirements. Selecting the correct file from a library with ready charge profiles, for quick and easy import via the charger's IR-Interface, will render the charger the customer wants.

Safety

Short circuit-, overload- and reverse polarity protection

Pmax	Chemistry	Cells	Imax	Input	Dimensions (mm)
750W	Li-Ion LiFePO4	7S - 14S 7S - 16S	25A	100 - 240 VAC 50 - 60 Hz	W * D * H: 225*190*105

Any other chemistry/cell number on request

YOUR GLOBAL PARTNER FOR POWER SOLUTIONS!

MEC-Energietechnik GmbH
Dorfstrasse 2, 9542 Afritz am See,
Austria, Europe

E-mail: office@mec-energietechnik.at
Tel: +43-(0)4247 30100-0
www.mec-energietechnik.com